



thermostats

WARMUP thermostats are constructed from the finest quality materials available and have been selected and developed for their ease of use, functionality and good looks...



Radiant Floor Heating

warmup[™]

thermostats

Specifications

programmable

TH115 (Air, Floor or Air with Floor Limitation)

Advanced temperature control ensures total comfort by minimising temperature swings

On/standby switch enables thermostat shutdown at the end of heating session for added security

Remote input works with phone or alarm system (telephone controller required)

On-screen heating command indicator gives at-a-glance verification of power being sent to the floor

Temporary bypass enables temperature override without changing programming

Floor model with easy-access floor sensor connector enables precise control of floor temperature

Large, backlit LCD features intuitive programming icons

Attractive design includes hidden programming buttons

Battery-free backup means no re-programming your schedule after power cuts.

non-programmable

TH114 (Air or Floor)

Sleek Contemporary design

Advanced temperature control ensures total comfort by minimising temperature swings

On/Standby switch enables thermostat shutdown at the end of the heating season for added security

Hidden adjustable temperature locks limit minimum and maximum setpoints

Remote input works with phone or alarm system (telephone controller required)

Push button means easy temperature setting

Floor model with easy-access floor sensor connector enables precise control of floor temperature

Battery-free

WP207 - F

Electronic thermostat

Remote floor sensor which is designed to meet the standard requirements for comfort, safety and energy saving

Locking mechanism behind the control knob to limit the amount of adjustment possible

PT503

Electronic thermostat equipped with a microprocessor. Depending on the selected mode, this thermostat has been designed to control:

A: Ambient temperature

F: Floor temperature (floor heating) 5 settings

pre-programmed

PT502

Electronic timing device

Advanced temperature control which allows the heating to be switched over a pre-programmed period

4 programmes

TH115 - programmable (Air, Floor or Air with Floor Limitation)

TH114 - non-programmable (Air or Floor)

Temperature control	Switching action	Programming (TH115 only)	Dimensions (h/w/d)
Microprocessor optimised PIA*	Epoxy-soundproofed relay: quiet operation	7-day independent programming, 4 settings/day	124 x 70 x 23mm Floor sensor: 4.6m
Heating cycles: 15 minutes	240 V 15 Amps - 50 Hz	Pre-programmed schedule or personalised	Fits over standard vertical flush box
Accuracy: $\pm 0.5^{\circ}\text{C}$		Early Start function	
Manual Dual scale: $^{\circ}\text{C}/^{\circ}\text{F}$		24-hour format	

PIA* - Proportional Integral Adaptive calculates the power requirement for every 15 minutes the heating is used.

WP207 - F

On/Off Temperature settings 5 to 40 $^{\circ}\text{C}$	230 - 240V 16 Amps - 50 Hz		114 x 81 x 20mm Fits over standard vertical flush box
--	-------------------------------	--	--

PT503

4 available setpoints to identify and select your comfort temperature	230 - 240V 15 Amps resistive - 50 Hz		114 x 70 x 18mm Fits over standard vertical flush box
---	---	--	--

PT502

4 programmes P1, P2, P3 and Manual	230 - 240V 15 Amps resistive - 50 Hz		114 x 70 x 18mm Fits over standard vertical flush box
---------------------------------------	---	--	--

product range

programmable



TH115



*With doors open



PT502

pre-programmed

non-programmable



TH114



WP207 - F



PT503

WARMUP has heating experts and contractors nationwide, who will be pleased to provide more details on WARMUP products and services.

To contact your local WARMUP distributor or to arrange a no-obligation free quotation, please call our freephone number.

Freephone
0800 WARMUP (927-687)

www.warmup.co.nz

Radiant Floor Heating

warmup[™]