



Warmup thermostats are constructed using high quality components and have been selected for their ease of use, functionality and good looks...

Thermostats

warmup[®]
Est. 1994

Underfloor heating | Tiled shower solutions

Thermostats

Programmable – TH115 (Air, Floor or Air with Floor Limitation)

Advanced temperature control ensures total comfort by minimising temperature swings

On/off switch enables thermostat shutdown at the end of heating session for added security

Remote input works with phone or alarm system (telephone controller required)

Temporary bypass enables temperature override without changing programming

Floor model with floor sensor connector enables precise control of floor temperature

Large, backlit LCD features intuitive programming icons

Battery-free backup means no re-programming your schedule after power cuts



Specifications

TEMPERATURE CONTROL	SWITCHING ACTION	PROGRAMMING	DIMENSIONS (H/W/D)
Microprocessor optimised PIA*	Epoxy soundproofed relay: for quiet operation	7-day independent programming, 4 settings / day	124 x 70 x 23mm
Heating cycles: 15 minute intervals Accuracy: ± 0.5°C Manual override Scale: Celsius (°C)	240 V 15 Amps ~ 50 Hz	Pre-programmed schedule or personalised Early Start function 24-hour format	Fits over standard vertical flush box

*PIA – Proportional Integral Adaptive calculates the power requirement for every 15 minutes the heating is used.

Programmable – WT01 & WT02 (WiFi) - Colour Touch Thermostats

Thermostat control – Electronic thermostat with temperature control via a sensor placed either externally in the floor or built into the thermostat.

Built-in clock/calendar with battery backup – Includes 4 and 6 event program for automatic comfort and setback temperature. Up to 7 different program combinations can be created.

Energy use – The Energy use function uses data to calculate electricity consumption and the cost of heating over a given period of time.



Specifications

TEMPERATURE CONTROL	SWITCHING ACTION	PROGRAMMING	DIMENSIONS (H/W/D)
Adaptive control for comfort temperature when required Heating cycles: 15 minute intervals Accuracy: ± 0.5°C Scale: Celsius (°C)	220-240V 16 Amps ~ 50 Hz	4 and 6 event program for automatic comfort and setback temperature 7 different program combinations 24-hour format Manual override	NZ: 115 x 84 x 40mm (Fits over standard vertical or horizontal flush box)



Non-programmable – MTC-1991-WU (floor) & MTC-1999UCH (air) Electronic thermostat

Remote floor sensor which is designed to meet the standard requirements for comfort, safety and energy saving.

Locking mechanism behind the control knob to limit the amount of adjustment possible

Specifications

TEMPERATURE CONTROL	SWITCHING ACTION	DIMENSIONS (H/W/D)
On/Off Temperature settings 10 to 50°C	230-240 V 16 Amps ~ 50 Hz	115 x 84 x 50mm Fits over standard vertical flush box

Warmup has heating experts and contractors nationwide, who will be pleased to provide more details on Warmup's products and services. To contact your local Warmup distributor or to arrange a free, no-obligation quotation, please call New Zealand: 0800 WARMUP (927 687) / Australia: 1300 138 126. www.warmup.co.nz



Underfloor heating | Tiled shower solutions